









Micro Transmitter RT21

Baseline

The Micro Transmitter RT21 is both, a 1- and 2-channel transmitter. Every transmitter is delivered with a unique code.

More than 70 million alternative codes ensure the uniqueness of every code.

The code can be transferred to any number of other transmitters simply at the push of a button, just as easy as duplicating a key.



RT21-XX0XM-01

			_		
Tec	hn	100		1012	110
I E C		La		- La	шэ.

Coding		factory coding with over 70 million options,	
		code duplication by the user is possible	
	Channels	1 or 2 (1 or 2 buttons)	
	Range	up to 150 m under favourable open field conditions	
	Power Supply	1x 3V battery, CR2032	
	Operation Indicator	LED	
	Control	transmission lasts for as long as button is pressed	
		(but max. 36 s)	
	Degree of Protection	IP54	
	Operating Temperature	-20 °C to +60 °C	
	Dimensions	55 x 36 x 16 mm	
	Weight	17 g (including battery)	

Accessories



ACC-CON-01

Scope of Delivery

- · Micro Transmitter incl. Battery
- · Programming Connector
- · Operating Manual

Accessories (optional)

· Battery

Models

iii o a o i o		
Product Key	Description	Frequency
on request	Micro Transmitter 1-Channel	315 MHz
on request	Micro Transmitter 2-Channel	315 MHz
RT21-4101M-01	Micro Transmitter 1-Channel	433,92 MHz
RT21-4102M-01	Micro Transmitter 2-Channel	433,92 MHz
RT21-5001M-01	Micro Transmitter 1-Channel	868,30 MHz
RT21-5002M-01	Micro Transmitter 2-Channel	868,30 MHz
on request	Micro Transmitter	916,50 MHz
ACC-CON-01	Programming Connector	
ACC-BAT-05	Battery CR2032	